

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 0 986 248 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
15.03.2000 Bulletin 2000/11

(51) Int Cl. 7: H04N 5/00, G11B 27/30

(21) Application number: 99250056.1

(22) Date of filing: 02.03.1999

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE
Designated Extension States:
AL LT LV MK RO SI

(72) Inventors:
• Ostermann, Ralf
30451 Hannover (DE)
• Keesen, Werner
30173 Hannover (DE)

(30) Priority: 07.09.1998 EP 98250316

(74) Representative: Hartnack, Wolfgang, Dipl.-Ing.
Deutsche Thomson-Brandt GmbH
European Patent Operations
Karl-Wiechert-Allee 74
30625 Hannover (DE)


(71) Applicant: DEUTSCHE THOMSON-BRANDT
GMBH
78048 Villingen-Schwenningen (DE)

(54) Method and apparatus for timestamping a bitstream to be recorded

(57) A settop box can be connected to a DVD Streamer via an IEEE1394 interface which contains means to timestamp data and to strip off these timestamps again, using them for timing regeneration. The DVD Streamer also must re-generate the timing of data packets as it was upon recording, when these packets are placed back. The streamer could also use own timestamps and strip them off again when replaying. So, in total, there is an in-series connection between two time stamping and time regeneration mechanisms which introduces jitter accumulation.

The settop box itself adds time stamps to the data packets before sending them through the IEEE1394 interface. These timestamps pass the IEEE1394 interface unnoticed, i.e. as part of the payload. These timestamps are used when the DVD Streamer plays back a stream. The advantage is that there is only one timing/regeneration process involved and that no jitter is accumulated.

As an alternative, the stream recorder uses the IEEE1394 timestamps and evaluates them when replaying in order to assign to the data packets the correct temporal position.



Description

[0001] The invention relates to a method and to an apparatus for timestamping a bitstream to be recorded or for using timestamps when replaying from a stream recorder, e.g. an optical disc recorder.

Background

[0002] Stream recording assumes an 'application device', e.g. a settop box, connected to a DVD Streamer. Both devices are connected via e.g. an IEEE1394 (IEC 611883) interface which in its transmitting and receiving firmware contains means to timestamp data and to strip off these timestamps again, using them for timing regeneration. The resulting effect is that this system behaves between the IEEE1394 interface input and the IEEE1394 interface output like a constant delay system.

Invention

[0003] A stream recorder must re-generate the timing of data packets as it was upon recording, when these packets are played back, so that between recording and playback this system also behaves like a constant delay system. In one embodiment of the invention the stream recorder adds its own timestamps to the data packets when recording and evaluates them when replaying in order to assign to the data packets the correct temporal position. Thereby the original data packet burst characteristic is reconstructed for a data stream having in principle non-equidistant data packets.

[0004] However, there is an in-series connection between two timestamping and time regeneration mechanisms which can introduce jitter accumulation. In a second embodiment of the invention the application device itself, before sending the data through the IEEE1394 interface, adds time stamps to the data packets. These timestamps may have the meaning of 'departure time' rather than 'arrival time' and pass the IEEE1394 interface 'unnoticed', i.e. from a IEEE1394 interface point of view they are part of the payload. At the other end of the chain these timestamps are used when the stream recorder plays back a stream. The advantage is that there is only one timing/regeneration process involved which has influence on the temporal position of the replayed data packets, and that therefore no jitter is accumulated. In this second embodiment the stream recorder does not make use of the IEEE1394 timestamps.

[0005] In a third embodiment the stream recorder records the IEEE1394 timestamps and evaluates them when replaying in order to assign to the data packets the correct temporal position.

[0006] It is one object of the invention to disclose a method for recording and replaying a bitstream, wherein after replaying the recorded data packets do have the correct temporal location within the bitstream and wherein no jitter accumulation takes place. This object is achieved by the methods disclosed in claims 1, 3 and 4.

[0007] It is a further object of the invention to disclose an apparatus which utilises the inventive method. This object is achieved by the apparatuses disclosed in claims 6, 7, 9 and 10.

[0008] In principle, the inventive method is suited for: timestamping a bitstream to be recorded or for using timestamps when replaying from a stream recorder, wherein a device or signal source outputting said bitstream to be recorded adds said timestamps to data packets of said bitstream and wherein the data packets of said bitstream pass to said stream recorder through a network which causes network jitter and for which network said timestamps belong to the payload of said data packets, and wherein said timestamps are used when replaying said data packets from said stream recorder in order to relocate the replayed data packets to the corresponding original temporal position in said bitstream,

or is suited for:

timestamping an MPEG bitstream to be recorded or for using timestamps when replaying from a stream recorder, wherein MPEG timestamps are included in data packets of said MPEG bitstream to be recorded and for the recording additional timestamps generated by said stream recorder become attached to the data packets of said MPEG bitstream to be recorded, and wherein said additional timestamps are used when replaying said data packets from said stream recorder in order to relocate the replayed data packets to the corresponding original temporal position in said MPEG bitstream,

or is suited for:

timestamping a bitstream to be recorded or for using timestamps when replaying from a stream recorder, wherein data packets of said bitstream pass to said stream recorder through a network which causes network jitter and which network internally adds network timestamps to data packets of said bitstream in order to reduce said jitter when outputting said data packets, and wherein said stream recorder records said network timestamps and during replay uses said recorded network timestamps in order to relocate the replayed data packets to the corresponding original temporal position in said bitstream.

[0009] Advantageous additional embodiments of the inventive method are disclosed in the respective dependent

claims.

[0010] In principle, the inventive apparatus is suited for timestamping a bitstream to be recorded and includes:

- program selection means which provide data packets from said bitstream, the data packets belonging to a specific program;
- a network interface which provides data of said data packets to a stream recorder or which receives data of said data packets from said stream recorder, wherein the related network causes network jitter and for which network said timestamps belong to the payload of said data packets and wherein said timestamps are used to relocate the replayed data packets to the corresponding original temporal position in said bitstream;
- means for generating timestamps and for adding these timestamps to the data of said data packets, which means provide the output data to said network interface;
- means for decoding replayed data of said data packets received from said network interface,

and concerns a Stream recorder for a bitstream, including:

- a network interface which provides data of data packets of said bitstream including timestamps, having been inserted outside said network interface, for recording or which receives replayed recorded data, wherein the related network causes network jitter and for which network said timestamps belong to the payload of said data packets;
- stream recording means which record data of said data packets including said timestamps or which replay data of said data packets, wherein during replay said timestamps are used in order to relocate the replayed data packets to the corresponding original temporal position in said bitstream before the replayed data packets enter said network interface,

or concerns a Stream recorder for a bitstream, including:

- a network interface which provides data of data packets of said bitstream, said data packets including MPEG timestamps, for recording or which receives replayed recorded data for data packets including said MPEG timestamps;
- stream recording means which record data of said data packets, including said MPEG timestamps, and additional timestamps generated by said stream recording means which become attached to the data packets of said MPEG bitstream to be recorded, or which replay data of said data packets, wherein during said replay said additional timestamps are used in order to relocate the replayed data packets to the corresponding original temporal position in said MPEG bitstream,

or concerns a Stream recorder for a bitstream, including:

- a network interface which provides data of data packets of said bitstream for recording or which receives replayed recorded data, wherein the related network causes network jitter and which network internally adds network timestamps to data packets of said bitstream in order to reduce said jitter when outputting said data packets;
- stream recording means which record data of said data packets including said network timestamps, or which replay data of said data packets, wherein during replay said network recorded timestamps are used in order to relocate the replayed data packets to the corresponding original temporal position in said bitstream before the replayed data packets enter said network interface.

[0011] Advantageous additional embodiments of the inventive apparatuses are disclosed in the respective dependent claims.

Drawings

[0012] Embodiments of the invention are described with reference to the accompanying drawings, which show in:

- Fig. 1 simplified block diagram of a settop box and a Stream recorder with IEEE1394 connection;
- Fig. 2 steps in the transmission of a transport stream;
- Fig. 3 structure of a stream pack;
- Fig. 4 structure of an application time stamp.

Exemplary embodiments

[0013] The following abbreviations are used in the description: DVD: digital versatile disc, LB: logical block, RBN: relative byte number, RBP: relative byte position, RLBN: relative logical block number, STB: set top box, TOC: table of content, SCR: system clock reference, SOB: stream object, DVD RTRW: DVD realtime rewritable, PES: packetised elementary stream, PTS: presentation timestamp, DTS: decoding timestamp, ATS: application timestamp.

[0014] In Fig. 1 transport streams are received by an antenna ANT and pass through a tuner TU selecting one of the transport streams, and through a demultiplexer DEM. Into the output signal of DEM time stamps can be inserted in a time stamp inserter TSI which receives the time stamps from a time stamp generator TS.

An application device which can be a DVD stream recorder including stream recording means STRREC, receives output data from DEM or TSI, respectively, via an IEEE1394 interface transmitter 1394TR and an IEEE1394 interface receiver 1394RECS. The data replayed from STRREC pass through an IEEE1394 interface transmitter 1394TRS and an IEEE1394 interface receiver 1394REC to decoder means DEC which deliver the final output signal or signals O. DEC may include a video decoder, one or more audio decoders and one or more additional data decoders.

[0015] Instead of an IEEE1394 connection any other network causing network jitter like the Ethernet or the Internet can be used.

[0016] TU, DEM, TS, TSI, 1394TR, 1394REC and DEC can be parts of a settop box. 1394RECS, STRREC and 1394TRS can be parts of a DVD stream recorder. Instead of a settop box any other data stream source can be used, e.g. a DVD player or a PC or Internet receiver. In that case ANT and TU is replaced by e.g. an optical disc and a pickup.

[0017] Fig. 2 depicts the temporal behaviour of certain items of the received PES stream with respect to the functional blocks in Fig. 1.

Fig. 2a shows a transport stream with multiplex of packets of programs A, B, C and D, and SI information at the output of TU in Fig. 1.

Fig. 2b depicts source packets of the selected program A with its relevant SI information at the output of DEM in Fig. 1. The black parts of the packets are the packet headers which include transmitted time stamps represented by the arrows.

Fig. 2c shows source packets at the output of the smoothing buffer inside IEEE1394 transmitter 1394TR which causes such a delay that the packets are now essentially equidistant.

Fig. 2d shows the source packets at the input of the IEEE1394 receiver 1394REC which introduces an additional delay, wherein it is assumed that no stream recorder is connected or that the stream recorder has no influence on the temporal location of the packets.

Fig. 2e depicts the reconstructed timing for the source packets at the output of 1394REC which again introduces an additional delay. One can see that time differences Δt_1 and Δt_2 of Fig. 2e finally correspond to that of Fig. 2b. The arrival time is the departure time plus the overall delay ODEL which is represented by a timestamp offset.

[0018] The clock frequency for transferring the bytes of a transport stream may be different in different applications. An IEEE1394 system uses segments having a length of 125 μ s, called cycle master packet. Within such cycle a data packet has a non-defined temporal position, i.e. a jitter range of maximum nearly 125 μ s is introduced. Therefore the IEEE1394 system makes use of its own 'timestamps' which serve to temporally correctly relocate the packets within the 125 μ s segments at the output of an IEEE1394 receiver.

The exact timing is important for a succeeding decoder because the decoder's buffer capacity is limited and an additional jitter in the data packets could cause buffer overflow or underflow and thereby erroneously decoded data.

An IEEE1394 transmitter includes a buffer at its input and an IEEE1394 receiver includes a buffer at its output, which smooth the average data rate. Additionally, in the IEEE1394 system a temporal compression of the data packets takes place which is apparent from the comparison of Fig. 2c and 2d. This compression also increases the maximum jitter at the demultiplexer output. In addition to the limited temporal resolution in the IEEE1394 system described above a further portion of jitter is added by the non-perfect 25MHz clock.

[0019] A proposed stream recorder specification offers the possibility to record stream-recorder generated timestamps which are derived from e.g. a 27MHz clock. In one embodiment of the invention the stream recorder records the IEEE1394 timestamps instead and evaluates them when replaying in order to assign to the data packets the correct temporal position.

[0020] The length of the data packets is programmable in the IEEE1394 system. Therefore in another embodiment of the invention the original 188 byte length of the transport stream packets is increased by e.g. 4 bytes to a total length of 192 bytes in order to add timestamps supplied from the application device, e.g. a settop box.

[0021] The DVD Stream Recording system is designed to use rewritable DVD discs for recording existing digital bitstreams, editing them and playing them back as bitstreams. This system is designed to satisfy the following requirements:

- Any packet size is supported as long as it is equal or less than 2kByte and is of constant length within a take.

- A timing mechanism, i.e. a time stamp is added to every broadcast packet to enable proper packet delivery during playback.
- To enlarge the fields of applications, non-real-time recording should be possible. However, in this case the STB has to generate the timestamp information.
- Data allocation strategy and a file system to support real-time stream recording.
- Many digital services require Service Information which normally is embedded in the real-time stream. To support a STB fed by data from a DVD player, the DVD should provide additional space, which can be used by the STB to duplicate part of the service information and to add additional TOC information.
- Copy Protection must be supported. In addition, any scrambling performed by the service provider or the STB must be kept unchanged.

[0022] User requirements can be grouped into requirements for recording, requirements for playback, and requirements for editing:

Real-time Recording

[0023] The system is designed to enable real-time recording of digital streams. It allows the user to concatenate recordings, even if those recordings consist of different stream formats. If recordings are concatenated, a seamless or close-to-seamless playback feature can be achieved, but is not required.

Navigation Support

[0024] To support navigation two pieces of information (lists) are generated during recording:

- 1) An 'original' version of a play list. This list contains quite low level information, e.g. time map or (broadcast) packet order of the recording. This list is accessible by the STB and the content is understood by the DVD streamer as well as by the STB. In its original version the playlist enables the playback of a complete recording. The playlist may be accessed and extended after recording by the STB to allow more sophisticated playback sequences.
- 2) The second piece of information, a mapping list, is generated to support the stream recorder to retrieve packet stream chunks (cells), that are described in terms of the application domain, e.g. 'broadcast packets' or 'time'. This list is owned and understood by the DVD streamer only.

Content Description

[0025] The system can reserve space which can be used by the STB to store high-level TOC and Service Information. This information is provided for the user to navigate through the content stored on disc and may contain sophisticated EPG information. The content needs not to be understood by the stream recorder. However a common subset of the TOC information, e.g. based on a character string, may be useful to be shared between STB and DVD, in order to enable the stream recorder to provide a basic menu by itself.

[0026] Playback of individual recording and playing all recordings sequentially is possible via a play list.

Player menus for entry point selection

[0027] The STB can generate a sophisticated menu based on the TOC information stored on the disc. A simple menu is generated by the streamer itself, e.g. via some 'character' information which is shared by STB and DVD.

Trick play modes

[0028] The STB can steer trick play via the 'play list'. Due to the nature of the broadcast stream, the trick play features may be limited to basic ones, e.g. Time Search and Title Jump. User defined playback sequence features like programming or parental control can be supported via the play list.

[0029] The DVD streamer creates the 'original version' of the play list. It can allow extensions and modifications of the play list by the STB for more sophisticated playback features. The DVD streamer is not responsible for the content of those sophisticated playlist(s).

The system supports the deletion of single recordings on user's request. Preferably the system allows this feature under the control of the STB.

The system may support insert editing.

[0030] Concerning the directory and file structure, the organisation of Stream Data and Navigation Data of DVD Stream Recording is done in a specific way such as to take into account the following:

- Any DVD Streamer device has certain requirements to store its own housekeeping data or Streamer-specific navigation data on the disc. These data are solely for helping the retrieval of recorded data; they need not be understood or even be visible to any outside application device AD.
- Any DVD Streamer device needs to communicate with the application device AD it is connected to. This communication is as universal as possible so that the maximum possible range of applications can be connected to the Streamer. The Navigation Data to support such communication are called Common navigation data and must be understandable by the Streamer as well as by the application device.
- The Streamer device offers to the connected application device AD a means for storing its own private data of any desired kind. The Streamer needs not to understand any of the content, internal structure, or meaning of this application-specific navigation data.

[0031] A possible directory and file structure is described below. The files storing the disc content are placed under the STRREC directory which is under the root directory. Under the STRREC directory the following files are created:

- COMMON.IFO
Basic information to describe the stream content. Needs to be understood by the Application Device as well as the Streamer.
- STREAMER.IFO
Private housekeeping information specific to the Streamer Device. Needs not to be understood by the Application Device.
- APPLICAT.IFO
Application Private Data, i.e. information that is specific to the Application(s) connected to the Streamer. Needs not to be understood by the Streamer.
- REALTIME.SOB
Recorded real-time stream data proper.

Note that except for the files described above, the STRREC directory shall not contain any other files or directories.

[0032] Stream Data include one or more 'Stream Objects' (SOBs) which each can be stored as a 'Program stream' as described in ISO/IEC 13818-1, Systems.

A SOB can be terminated by a program_end_code. The value of the SCR field in the first pack of each SOB may be non-zero.

A SOB contains the Stream Data packed into a sequence of 'Stream Packs' (S_PCKs). Stream data can be organised as one elementary stream and are carried in PES packets with a stream_id.

In Stream recording, the application performs its own padding so that the pack length adjustment methods of DVD-ROM Video or RTRW need not to be used. In Stream recording it is safe to assume, that the Stream packets will always have the necessary length.

[0033] As shown in Fig. 3, a Stream Pack has 2048 bytes and includes a pack header followed by a Stream PES Packet. A system header may be included in those S_PCKs which are the first S_PCK of a SOB. When a system header is included the length of the remaining Stream PES Packet content may be 2010 bytes, and when not included, 2034 bytes. A pack is recorded in one LB. The pack header may include the following items of data:

Field	Number of bits	Number of bytes	Value	Comment
Pack_start_code	32	4	0000 01BAh	

(continued)

Field	Number of bits	Number of bytes	Value	Comment
'01'	2	6	provider defined	01b
SCR_base[32..30]	3			(Note 1)
marker_bit	1			1
SCR_base[29..15]	15			
marker_bit	1			1
SCR_base[14..0]	15			
marker_bit	1			1
SCR_extension	9			
marker_bit	1		1	
program_mux_rate	22	3	01 3883h	mux_rate = 8Mbps (Note 2)
marker_bit	1			1
marker_bit	1			1
reserved	5	1	F8h	11111b
pack_stuffing_length	3			no stuffing length = 000b
Note 1: 'SCR_base[32]' is set to ZERO.				
Note 2: 'program_mux_rate' is set to 8Mbps.				

[0034] In a Stream PES Packet, the stream PES packet header content is identical to that defined in the DVD standard, with the following limitations and additional rules:

- The 'stream_id' field is set to 0xBD (private_stream_1)
- The total length of the stream PES packet header is 14 bytes. Therefore the 'PES_header_data_length' field is set to 5 bytes.
- Each stream PES packet header carries a PTS timestamp. DTS timestamps are not encoded. Therefore the 'PTS_DTS_flags' is set to '10b'.
- The 'PES_packet_length' includes any reserved bytes behind the last Application transport packet up to the end of the streamer DVD pack. Therefore the 'PES_packet_length' is always 2028 bytes.
- No padding PES packet shall be encoded in a streamer DVD pack. Padding is described below in the 'application header'.

[0035] The Stream PES packet header may include the following items of data:

Field	Number of bits	Number of bytes	Value	Comment
packet_start_code_prefix	24	3	000001h	
stream_id	8	1	1011 1101b	private_stream_1
PES_packet_length	16	2	07 ECh	2028

(continued)

	Field	Number of bits	Number of bytes	Value	Comment
5	'10'	2	3	10b	
	PES_scrambling_control	2			
	PES_priority	1		0	no priority
	data_alignment_indicator	1		0	not defined by descriptor
10	copyright	1		0	not defined by descriptor
	original_or_copy	1		0	copy
	PTS_DTS_flags	2		10b	
15	ESCR_flag	1		0	no ESCR field
	ES_rate_flag	1		0	no ES rate field
	DSM_trick_mode_flag	1		0	no trick mode field
	additional_copy_info_flag	1		0	no copy info field
20	PES_CRC_flag	1		0	no CRC field
	PES_extension_flag	1		0	no extension
	PES_header_data_length	8		05h	5
25	'0001'	4	5	Provider defined	
	DTS[32..30]	3			
	marker_bit	1			
	DTS[29..15]	15			
30	marker_bit	1			
	DTS[14..0]	15			
	marker_bit	1			
35	stuffing byte	0	0		
	Private data area				
	sub_stream_id	8	1		
40	Stream Data Area				

[0036] Fig. 3 also shows that the Stream Data Area inside a Stream PES Packet includes an application header, an application header extension and a sequence of application packets, each prefixed by an application packet timestamp. The Application Header may include the following items of data:

	Field	Number of bits	Number of bytes	Value	Comment
45	(1) VERSION	8	1	01h	
	(2) APPLICATION_ID	16	2		
50	(3) MAX_BITRATE	32	4		
	(4) SMOOTH_BUF_SIZ	16	2	'3540 bytes'	
55	(5) TS_REF_CLK_FREQ	32	4	'27 MHz'	
	(6) AP_PKT_LEN	16	2		
	(7) TS_LEN	8	1	04h	4

(continued)

Field	Number of bits	Number of bytes	Value	Comment
(8) AP_PKT_Ns	8	1		
(9) START_OF_STR	1	1	0b or 1	
(10) END_OF_STR	1		0b or 1b	
reserved	6		111111b	
reserved	56	7	7x(FFh)	
	Total	25		
(1) VERSION describes the version number of the application header format. (2) APPLICATION_ID describes the application that generated the stream. If the application is unknown, 0x0000 is encoded. (3) MAX_BITRATE describes the output bitrate parameter of the leaky bucket flow control model in Mbps. (4) SMOOTH_BUF_SIZ describes the buffer size parameter of the leaky bucket flow control model. (5) TS_REF_CL_FREQ describes the reference clock frequency of the packet arrival/delivery timestamp. (6) AP_PKT_LEN describes the length of the application packet, excluding the timestamp, in bytes. (7) TS_LEN describes the length of the timestamp field in bytes and is set to the value '4'. (8) AP_PKT_Ns is the number of application packets in this Stream PES Packet DVD pack: AP_PKT_Ns = 1, 2, ..., 487 div AP_PKT_LEN (9) START_OF_STR: when set to '1', this Stream PES Packet is the first DVD pack in the stream. (10) END_OF_STR: when set to '1', this Stream PES Packet is the last DVD pack in the stream.				

[0037] The application header extension includes a list of entries, where there is exactly one entry of 1 byte for each Applicationtransport layer Packet. These bytes are used to store information that may differ from application packet to application packet. The total length of the application header extension is 46 bytes. The first 'AP_PKT_Ns' entries of these carry valid data. Unused list entries may carry undefined values. The total length of 'application header' and 'application header extension' is 71 bytes.

Field	Number of bits	Number of bytes	Value	Comment
(1) AU_START	1	1		
(2) AU_END	1			
(3) reserved	4			
(4) COPYRIGHT	2			
(1) AU_START: when set to '1', indicates that the associated application packet contains a random access entry point into the stream				
(2) AU_END: when set to '1', indicates that the associated application packet is the last packet of a random access point.				
(4) COPYRIGHT describes the copyright status of the associated application packet.				

[0038] The application timestamps ATS of each application packet are represented by a 32 bit value. An ATS is divided into a base part and an extension part. The base part represents the 90kHz unit value, and the extension part represents the less significant value measured in 27MHz units:

$$0 \leq \text{ATS_exten} < 300. \text{ ATS in seconds} = \text{ATS_base}/90\text{kHz} + \text{ATS_exten}/27\text{MHz}.$$

[0039] Together, ATS_base and ATS_exten cover a range of more than 93 seconds.

The application timestamp describing format is depicted in Fig. 4.

[0040] The numbers and parameters given in this description are examples and can be adapted correspondingly to other applications of the invention.

Claims

1. Method for timestamping a bitstream (A, B, C, D, SI) to be recorded or for using timestamps when replaying from a stream recorder (STRREC), wherein a device (TU, DEM, TS, TSI, DEC) or signal source outputting said bitstream to be recorded adds (TSI) said timestamps (TS) to data packets of said bitstream (A, SI) and wherein the data packets of said bitstream pass to said stream recorder through a network (1394TR, 1394RECS, 1394TRS, 1394REC) which causes network jitter and for which network said timestamps belong to the payload of said data packets, and wherein said timestamps are used when replaying said data packets from said stream recorder in order to relocate the replayed data packets to the corresponding original temporal position in said bitstream.
2. Method according to claim 1, wherein said network is an IEEE1394 connection or is an Ethernet or is the Internet.
3. Method for timestamping an MPEG bitstream (A, B, C, D, SI) to be recorded or for using timestamps when replaying from a stream recorder (STRREC), wherein MPEG timestamps are included in data packets (A, SI) of said MPEG bitstream to be recorded and for the recording additional timestamps generated by said stream recorder become attached to the data packets of said MPEG bitstream to be recorded, and wherein said additional timestamps are used when replaying said data packets from said stream recorder in order to relocate the replayed data packets to the corresponding original temporal position in said MPEG bitstream.
4. Method for timestamping a bitstream (A, B, C, D, SI) to be recorded or for using timestamps when replaying from a stream recorder (STRREC), wherein data packets (A, SI) of said bitstream pass to said stream recorder through a network (1394TR, 1394RECS, 1394TRS, 1394REC) which causes network jitter and which network internally adds network timestamps to data packets of said bitstream in order to reduce said jitter when outputting said data packets, and wherein said stream recorder records said network timestamps and during replay uses said recorded network timestamps in order to relocate the replayed data packets to the corresponding original temporal position in said bitstream.
5. Method according to claim 4, wherein said network is an IEEE1394 connection.
6. Apparatus for timestamping a bitstream (A, B, C, D, SI) to be recorded, including:
 - program selection means (TU, DEM) which provide data packets (A, SI) from said bitstream, the data packets belonging to a specific program;
 - a network interface (1394TR, 1394REC) which provides data of said data packets to a stream recorder or which receives data of said data packets from said stream recorder, wherein the related network causes network jitter and for which network said timestamps belong to the payload of said data packets and wherein said timestamps are used to relocate the replayed data packets to the corresponding original temporal position in said bitstream;
 - means (TS, TSI) for generating timestamps and for adding these timestamps to the data of said data packets, which means provide the output data to said network interface;
 - means (DEC) for decoding replayed data of said data packets received from said network interface.
7. Stream recorder for a bitstream (A, B, C, D, SI), including:
 - a network interface (1394RECS, 1394TRS) which provides data of data packets (A, SI) of said bitstream including time-stamps, having been inserted outside said network interface, for recording or which receives replayed recorded data, wherein the related network causes network jitter and for which network said timestamps belong to the payload of said data packets;
 - stream recording means (STRREC) which record data of said data packets including said timestamps or which replay data of said data packets, wherein during replay said timestamps are used in order to relocate the replayed data packets to the corresponding original temporal position in said bitstream before the replayed data packets enter said network interface.
8. Apparatus according to claim 6 or 7, wherein said network is an IEEE1394 connection or is an Ethernet or is the Internet.
9. Stream recorder for an MPEG bitstream (A, B, C, D, SI), including:

- a network interface (1394RECS, 1394TRS) which provides data of data packets (A, SI) of said bitstream, said data packets including MPEG timestamps, for recording or which receives replayed recorded data for data packets including said MPEG timestamps;
- stream recording means (STRREC) which record data of said data packets, including said MPEG timestamps, and additional timestamps generated by said stream recording means which become attached to the data packets of said MPEG bitstream to be recorded, or which replay data of said data packets, wherein during said replay said additional timestamps are used in order to relocate the replayed data packets to the corresponding original temporal position in said MPEG bitstream.

5

10 10. Stream recorder for a bitstream (A, B, C, D, SI), including:

- a network interface (1394RECS, 1394TRS) which provides data of data packets (A, SI) of said bitstream for recording or which receives replayed recorded data, wherein the related network causes network jitter and which network internally adds network timestamps to data packets of said bitstream in order to reduce said jitter when outputting said data packets;
- stream recording means (STRREC) which record data of said data packets including said network timestamps, or which replay data of said data packets, wherein during replay said recorded network timestamps are used in order to relocate the replayed data packets to the corresponding original temporal position in said bitstream before the replayed data packets enter said network interface.

15

20

11. Stream recorder according to claim 10, wherein said network is an IEEE1394 connection.

25

30

35

40

45

50

55




Fig. 2




Fig. 1




Fig. 3




Fig. 4



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 99 25 0056

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION
X	US 5 689 507 A (VLOT MARNIX C ET AL) 18 November 1997 (1997-11-18) * column 8, line 1-24 *	1,2,6-8	H04N5/00 G11B27/30
X	EP 0 710 021 A (HITACHI LTD) 1 May 1996 (1996-05-01) * column 11, line 46 - column 16, line 16 *	1,6,7	
X	WO 97 00579 A (DIESS MICHAEL SCOTT ;BLATTER HAROLD (US); BEYERS WILLIAM WESLEY JR) 3 January 1997 (1997-01-03) * page 3, line 10 - page 13, line 10 *	1,6,7	
X	SAEIJS R W J J ET AL: "AN EXPERIMENTAL DIGITAL CONSUMER RECORDER FOR MPEG-CODED VIDEO AN EXPERIMENTAL DIGITAL CONSUMER RECORDER FOR MPEG-CODED VIDEO SIGNALS. SIGNALS" IEEE TRANSACTIONS ON CONSUMER ELECTRONICS, vol. 41, no. 3, 1 August 1995 (1995-08-01), pages 651-660 651, XP000539519 ISSN: 0098-3063 * page 653, left column - page 654, left column: paragraphs 3.1 and 3.2	3,9	
X	US 5 579 183 A (SAEIJS RONALD W J J ET AL) 26 November 1996 (1996-11-26) * column 4, line 45 - column 5, line 23 *	3,9	
X	EP 0 774 753 A (VICTOR COMPANY OF JAPAN) 21 May 1997 (1997-05-21) * column 12, line 49 - column 22, line 17 *	3,9	
A		1,6,7	
		-/--	
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 3 August 1999	Examiner Mourik, J
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

EPO FORM 1503 03/82 (P4/C01)



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 99 25 0056

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION
X	EP 0 749 244 A (MATSUSHITA ELECTRIC IND CO LTD) 18 December 1996 (1996-12-18) * the whole document *	4,10,11	
A	BANKS D ET AL: "BREAKING OPEN THE SET TOP BOX" PROCEEDINGS OF THE SPIE, vol. 3228, 4 November 1997 (1997-11-04), pages 105-116, XP002064906 * the whole document *		
A	BLOKS R H J: "The IEEE-1394 high speed serial bus" PHILIPS JOURNAL OF RESEARCH, vol. 50, no. 1, 1 January 1996 (1996-01-01), page 209-216 XP004008212 ISSN: 0165-5817 * the whole document *		
			TECHNICAL FIELDS SEARCHED
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 3 August 1999	Examiner Mourik, J
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

EPO FORM 1503 03 82 (P4/C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 99 25 0056

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

03-08-1999

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5689507 A	18-11-1997	EP 0723732 A	31-07-1996
		EP 0717909 A	26-06-1996
		WO 9602098 A	25-01-1996
		WO 9601540 A	18-01-1996
		JP 9502851 T	18-03-1997
		JP 9502854 T	18-03-1997
		US 5633871 A	27-05-1997
EP 0710021 A	01-05-1996	JP 8125971 A	17-05-1996
		JP 8336131 A	17-12-1996
		CN 1132442 A	02-10-1996
		EP 0891082 A	13-01-1999
		SG 34287 A	06-12-1996
WO 9700579 A	03-01-1997	AU 5924996 A	15-01-1997
		AU 5929096 A	15-01-1997
		CN 1192838 A	09-09-1998
		CN 1193442 A	16-09-1998
		EP 0832535 A	01-04-1998
		EP 0832536 A	01-04-1998
		WO 9700580 A	03-01-1997
		US 5841987 A	24-11-1998
US 5579183 A	26-11-1996	AU 692235 B	04-06-1998
		AU 1821895 A	30-10-1995
		AU 688868 B	19-03-1998
		AU 1822095 A	30-10-1995
		AU 701481 B	28-01-1999
		AU 6079498 A	18-06-1998
		BR 9505873 A	29-12-1998
		EP 0702879 A	27-03-1996
		EP 0702877 A	27-03-1996
		EP 0858230 A	12-08-1998
		FI 955887 A	07-12-1995
		HU 73451 A	28-08-1996
		WO 9527977 A	19-10-1995
		WO 9527978 A	19-10-1995
		JP 9505195 T	20-05-1997
		JP 8511413 T	26-11-1996
		PL 311953 A	18-03-1996
		US 5596581 A	21-01-1997
		US 5566174 A	15-10-1996
EP 0774753 A	21-05-1997	JP 9139914 A	27-05-1997
		JP 9186665 A	15-07-1997
		JP 9204738 A	05-08-1997

EPO FORM P4459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.

EP 99 25 0056

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

03-08-1999

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0774753 A		CN 1156880 A	13-08-1997
EP 0749244 A	18-12-1996	JP 9009217 A	10-01-1997
		JP 9046376 A	14-02-1997

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office. No. 12/82

THIS PAGE BLANK (USPTO)